

T-300 Automatic Tabletop Bagger

Our smallest, fully automatic bagger offers increased production capabilities. We pack a lot of features into this bagger, including touch-screen operation, "pop-up" messaging, job save/recall and automatic/paced operation.

Automatic indexing, sealing, tear-off or continuous strips of bags are possible.

CAUTION

Available options include the BF-10 Bag Deflator, CF-10 Counting Funnel, CS-10 Compartment Seal, LS-10/LS-15 Load Shelves, BL-10 Blow Off Assembly, Hand Scanners, Stainless Steel Funnels and Height-Adjustable Cart with Quick Change Bag Bars (shown below).



Height-Adjustable Cart

T-300 & T-375 Special Features:

- Full color screen with pop-up windows •
- Diagnostic and troubleshooting screens
- Preset and totalizing bag counter Automatic "paced" operation with fill time delay timer
- Universal, adjustable parts chute
- Adjustable support shelf
 Blower with flow controls
- · One year limited parts warranty

T-375 Automatic Tabletop Bagger/Printer "Next Bag Out"

In addition to all the features of the T-300, the T-375 incorporates a thermal transfer printer for "Next-Bag-Out" printing. This patented feature allows for printing just prior to loading, which guarantees accurate labeling and allows for quick changeovers on even the smallest batches. The seamless transition is also perfect for pharmaceutical applications when accurate labeling is vital.







Actual Bag Samples



Description Seal mechanism Cycle operation Guard-switch feature Product pass-through Electric Dimensions Specifications

T-300/T-375 1/8" Solid heater bar (thermocouple controlled) Manual/Automatic Standard 3" (can be increased) 110V/60hz (220V/230V, 50/60hz) 22" wide x 20" deep x 22" high

T-300 Cycle rate Up to 50 bags per minute Bag size range 2" x 2" up to 11" x 16" Index speed 25" per second Air* 50psi Weight 110 lbs * An "air-free" model is also available. T-375 Up to 30 bags per minute 2" x 3" up to 11" x 16" 12" per second (with printer on) 60psi 125 lbs

T-375 Printer Specifications: Zebra 110Xi IV Series Printer, 203 dpi 305 dpi and 600 dpi, optional 4" x 12" print area or 5" x 12", optional Built in memory for storage (999 labels) 16 MB SDRAM; 8 MB non-volatile Flash memory