

Click here for more information!



IPSi INTEGRATED
PRODUCTIVITY
SYSTEMS

(844) 477-4911 | www.ipsiscan.com



TX210 Series Desktop Barcode Printer

An Advanced Printer You Can Rely On

The TX210 series is comprised of high-performance desktop label printers designed to handle a wide variety of applications ranging from high-volume shipping label production to safety signage and fine-jewelry label printing.

The TX210 series features a user friendly design, media and ribbons are easy to install. The printers use a large 300 meter ribbon supply on a one inch core that saves both time and money. The TX210 Series can print at super-fast print speeds up to 8-inches per second with an easy-to-read multi-icon LED display (standard) and available in a color LCD display.

Supports more applications in its class including standalone, high-resolution 600 dpi product marking and graphics, and specialized electronics label marking applications. The TX210 series with built-in Ethernet or optional 802.11 a/b/g/n/ac Wi-Fi paired with SOTI Connect and TSC Console remote printer management increases your level of productivity and efficiency.

Key Features



Dynamic Remote Printer Management

- Supports SOTI Connect through either Ethernet or Wi-Fi
- Powerful TSC Console for printer management



Rugged Design

- Rugged design with solid double wall housing structure, ADF hinge and industrial-grade hybrid motor ensures stable media path for outstanding print quality and accuracy



Multi-Connectivity

- Wi-Fi enterprise certified 802.11 a/b/g/n/ac with Bluetooth 4.2 combo module
- MFI certified Bluetooth 5.0



Easy-to-Use UI

- LED icon panel with large status icons
- View angle adjustable 3.5" color LCD display
- Automatic centering label holder for 5" OD media roll with 1" or 1.5" core
- Enhanced ribbon stop mechanism prevents ribbon rewind issues when top cover is opened



Advanced TPH Mechanism

- Heat line adjustment mechanism supports various media types
- Self-Diagnostic TPH Care scans and detects printhead bad dots in real-time

Applications



Manufacturing

- Product Marking
- Compliance Labeling
- Inventory Control



Transportation and Logistics

- Shipping Label
- Receiving Label



Healthcare

- Specimen Labeling
- Pharmacy Labeling
- Patient Tracking

TX210 Series | Data Sheet

Model	TX210	TX310	TX610
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	24 dots/mm (600 DPI)
Printing method	Thermal Transfer & Direct Thermal		
Max. print speed	203 mm (8")/second	152 mm (6")/second	102 mm (4")/second
Max. print width	108 mm (4.25")	106 mm (4.17")	106 mm (4.17")
Max. print length	25,400 mm (1000")	11,430 mm (450")	2540 mm (100")
Enclosure	Clamshell with double-walled plastic		
Physical dimension	226 mm (W) x 198 mm (H) x 332 mm (D) 8.90" (W) x 7.80" (H) x 13.07" (D)		226 mm (W) x 200 mm (H) x 332 mm (D) 8.90" (W) x 7.87" (H) x 13.07" (D)
Weight	3.75 kg (8.27 lbs)		4.08 kg (8.99 lbs)
Label roll capacity	127 mm (5") OD		
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside)		
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")		
Processor	32-bit RISC CPU		
Memory	<ul style="list-style-type: none"> 128 MB Flash memory 128 MB SDRAM microSD card reader for Flash memory expansion, up to 32 GB 		
Interface	<ul style="list-style-type: none"> USB 2.0 RS-232 USB Host Internal Ethernet, 10/100 Mbps Centronics (factory option) 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module (dealer option) MFi Bluetooth 5.0 (factory option) 		
Power	External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 3.75A, 90W		External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 5.41A, 130W
Operation switch, button, LED/LCD	<ul style="list-style-type: none"> 1 power switch 1 feed/pause button LED panel with 8 big icons 		<ul style="list-style-type: none"> 1 power switch 6 operation buttons 3.5" color TFT display, 320 x 240 pixel
Sensors	<ul style="list-style-type: none"> Transmissive gap sensor Black mark reflective sensor (position adjustable) Ribbon encode sensor Head open sensor 		<ul style="list-style-type: none"> Transmissive gap sensor Black mark reflective sensor (position adjustable) Ribbon end sensor Ribbon encode sensor Head open sensor
Real time clock	Dealer option		Standard
Internal font	<ul style="list-style-type: none"> 8 alpha-numeric bitmap fonts Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font 		
Bar code	<ul style="list-style-type: none"> 1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D bar code TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode) 		
Font and barcode rotation	0, 90, 180, 270 degree		
Printer language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)		
Media type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)		
Media width	19 ~ 112 mm (0.75" ~ 4.4")		
Media thickness	0.055 ~ 0.254 mm (2.17 ~ 10 mil)		
Media core diameter	25.4 ~ 38.1 mm (1" ~ 1.5")		
Label length	3 ~ 25,400 mm (0.1" ~ 1,000")	3 ~ 11,430 mm (0.1" ~ 450")	3 ~ 2,540 mm (0.1" ~ 100")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing		
Safety regulation	FCC Class B, CE Class B, RCM, UL, cUL, TÜV/Safety, CCC, BIS, EAC, ENERGY STAR®		
Environmental concern	Comply with RoHS, WEEE		
Accessories	<ul style="list-style-type: none"> Quick start guide USB cable Power cord External universal switching power supply Windows labeling software CD disk 		
Limited warranty	<ul style="list-style-type: none"> Printer: 2 years Print head: 25 km (1 million inches) or 12 months which comes first Platen: 50 km (2 million inches) or 12 months which comes first 		
Factory options	<ul style="list-style-type: none"> Centronics parallel interface 3.5" color TFT display (includes real time clock) Ribbon end sensor MFi Bluetooth 5.0 		<ul style="list-style-type: none"> Centronics parallel interface MFi Bluetooth 5.0
Dealer options	<ul style="list-style-type: none"> Real time clock Peel-off module Guillotine cutter (full cut) 802.11 a/b/g/n/ac Wi-Fi with Bluetooth 4.2 combo module 		
User options	<ul style="list-style-type: none"> External label roll mount KP-200 Plus keyboard display unit 		



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +1 52 (33) 3673 1406
E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 3554 7225
E-mail: americas_sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 000
E-mail: emea_sales@tscprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 495 646 3538
E-mail: emea_sales@tscprinters.com

Middle East

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

INDIA

TSC India Distributor's Office
Tel: +91 2249 679 315
E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com

KOREA

TSC Korea Representative Office
Tel: +82 2 852 3322
E-mail: apac_sales@tscprinters.com

Product models and specifications are subject to change without notice.



TSC Printronix Auto ID tscprinters.com



TSC Printronix Auto ID Training Academy



Service and Maintenance



Click here for more information!



(844) 477-4911 | www.ipsiscan.com