



CT4-LX-HC

4-inch Desktop Printer for Healthcare

Healthcare Dedicated

- Clinical-ready anti-microbial plastic casing
- Conducive for the use of disinfectant cleansers




Expedite Patient Workflows

- Specimen Labels
- Pharmacy Labels
- Bloodbag Labels
- Identification Wristbands



Efficient & Cost Effective

- On-board printer language emulations
- Auto-clone printer settings
Backup or duplicate settings on a USB flash drive
- PDF Direct Print
Print PDF formats directly from the printer, no driver required.



Functional Design

- One-touch media profile recall
Register settings of commonly printed label types.
- Label waste prevention
Print from the first label and eliminate label loss.
- 4.3" full-color touchscreen



Click here for more information!



(844) 477-4911 | www.ipsiscan.com

www.satoamerica.com/CT4-LX-HC



GENERAL SPECIFICATIONS / CT4-LX-HC

PRODUCT SPECIFICATIONS

Print Resolution		203 dpi	305 dpi
Print Speed		8 ips	6 ips
Print Area	Max Width	4.09" (104mm)	
	Max Length	98.43" (2500mm)	59.06" (1500mm)
Media Size (with liner)	Width	Standard	0.98" - 4.65" (25 - 118mm)
		Continuous	0.39" - 15.74" (10 - 400mm)
	Length	Tear-off	0.98" - 15.74" (25 - 400mm)
		Cutter	0.91" - 15.74" (23 - 400mm)
		Dispenser	0.91" - 15.74" (23 - 400mm)

PRINTING SPECIFICATIONS

Method

Thermal Transfer (with Direct Thermal capability)

Mode

Continuous, Tear-off, Cutter, Dispenser

MEDIA SPECIFICATIONS

Sensor Type

Transmissive Sensor for Gap, Reflective Sensor for Black Mark, Paper Out, Ribbon Out

Media Type

Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket

Media

Thickness (Label & Liner)

0.0031" - 0.075" (0.08 - 0.19mm)

Roll Diameter

Maximum: 5.04" (128mm) on 1.5" core

Wind

Face-in / Face-out

Ribbon

Length

328' (100m) on 0.5" ID Core

Width

1.77" - 4.37" (45 - 111mm)

Roll Diameter

1.5" (40mm)

Wind

Face-out

SATO Genuine Consumables

For maximum print quality and optimum use, SATO recommends the use of SATO genuine consumables.

FONT SPECIFICATIONS

Internal Fonts

16 Bitmap SATO Fonts, 40 Scalable SATO Fonts, Multi-National Language Support (47 Languages/Unicode), Single and Double Byte Fonts (Korean, Chinese, Japanese)

CONNECTIVITY

Standard

USB 2.0 (Type A, Type B), Ethernet (DHCPv4/DHCPv6), NFC

Optional Interfaces

Wi-Fi and Bluetooth Ver 4.1 (Wi-Fi® and Wi-Fi Direct® Certified IEEE 802.11ac, Dual Band (2.4 GHz, 5 GHz))

MEMORY & PROCESSING

Printer Memory

4GB Flash, 1GB RAM

User Downloadable Fonts, Videos, Graphics or Format

Maximum 1GB

USER FRIENDLY SUPPORT TOOLS

Large Status LED

Blue / Red

Audible Alerts

Adjustable Volume Setting

Self Diagnosis

Head Check, Stand-by Mode, Cover Open, Test Print, Auto-Calibration, Label End, Ribbon Near-End and End

Display Panel

4.3" Full Color Resistive Touch Screen

Tool-Free Maintenance

Print Head and Platen Replacement

Multi-national Language Support

47 Printable Languages with Scalable Fonts
31 LCD menu languages

Operation Videos

Multiple Instructional Videos On-board, Space for Customized Videos

Emulation

Auto Detect - SBPL®, SEPL®, SZPL®, SDPL®, SIPL® or STCL® (Pre-installed), XML, PDF Direct Printing*, AEP*
*Contact your SATO Sales Representative for more information/requirements

Remote Maintenance

SNMP Ver. 3, Web Interfaces, SATO Online Services (SOS), All-In-One Tool (AIOT), SOTI Connect

OPTIONS

Cutter, Real-Time Clock, Wireless LAN and Bluetooth

BARCODE SYMBOLOGIES

Barcodes

Linear

Code 39, Code 93, Code 128, CODABAR (NW7), EAN8/13, GS1-Databar™, GS1-128 (UCC/EAN128), Interleaved 2/5, Industrial 2/5, JAN 8/13, Matrix 2/5, MS1, Bookland, Postnet™, UPC-A/E

2D Symlogies

PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, QR Code, Micro QR Code and Composite Symlogies, Aztec

OPERATING CHARACTERISTICS

Electrical Requirements

AC100V ~ AC240V ± 10%, 50/60 Hz (AC adapter)
Output: DC24V ± 5.0% 2.7A

Standards & Agency Approvals

Please contact SATO regarding agency approvals in your region.

Environment

Operating

32 - 104°F (0 - 40°C) / 30 - 80% RH (without condensation)

Storage

14 - 140°F (-10 - 60°C) / 15 - 90% RH (without condensation)

PHYSICAL CHARACTERISTICS

Dimensions

9.37" L x 7.0" W x 8.43" H (238mm x 177.8mm x 214.1mm)

Weight

7.5 lbs (3.4kg)

Finishing

Disinfectant-ready and anti-microbial casing

MISCELLANEOUS

Functions - Useful Features

Standalone Printing with SATO Application Enabled Printing (AEP), SATO Online Services (SOS), Multiple Interfaces-Auto-Switching, Auto Clone, Status Return, Label Waste Prevention

Rotation

Auto-label Rotation: 0°, 90°, 180°, 270°

SATO AMERICA CORPORATE

14125 South Bridge Circle
Charlotte, NC 28273

Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com/CT4-LX-HC

©2021 SATO America. All rights Reserved. Rev B • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.