

# MB241 Series

## Industrial Label Printer

### Rugged Space-Saver for Heavy Duty, Diverse Printing

The MB241 boasts a bifold media door, cutting operational space requirements by 24%. Its all-metal print mechanism guarantees durability in high-volume printing. The MB241 Series handles special media types like harder and thicker hangtags and is available with a wide range of optional accessories to support diverse applications. These accessories include linerless kits, peel-off kit, internal rewinder kit, and cutter, all designed to enhance functionality and meet dynamic business demands.

The printer capabilities are designed with auto-switching emulation for hassle-free deployment. TSC Standalone Creator generates a printer LCD UI for quick template access, while TSCPRTGo acts as an extended display for mobile printing. SOTI Connect, TSC Console, and the Internal Embedded Webpage enable remote fleet management.

The eco-friendly MB241 printer boasts 100% recyclable packaging and printer casing, with over 90% recyclable components, minimizing its environmental impact. It's ideal for limited space and excels in print quality and versatility, making it an outstanding choice for various printing needs.

## Key Features

### Optimized Space Efficiency

- The bifold door reduces space usage by 24%, streamlining media, ribbon replacement, and cleaning for efficient operations in limited space.

### High-Quality Printing Assurance

- A robust all-metal print mechanism on a metal frame guarantees printing stability and printer longevity.
- Equipped with features to adjust the multi-point thermal printhead (TPH) pressure and heat line, it ensures consistent, high-quality printing.

### Fits Diverse Applications Requirements

- Options like linerless kits, cutter, internal rewinder kit, and peel-off kit enhance printer versatility and cater to diverse needs.
- Connectivity options like MFi Bluetooth 5.0, Wi-Fi Bluetooth combo, and Bluetooth 5.0 offer flexibility for diverse applications.

### TSC Sense Care Smart Monitoring

- TSC Sense Care prevents downtime by monitoring printhead health with self-diagnostic TPH Care, printhead mileage, and cutter counts.
- Collected data can integrate with SOTI Connect and TSC Console for remote management and reporting.

### Software Capabilities Harmonize Operations

- Auto-switch printer language emulation simplifies printer fleet migration and upgrades without changing print commands and label templates.
- TSC Standalone Creator generates a printer LCD UI for quick template access and TSCPRTGo turns a mobile device into an extended display for mobile printing.
- SOTI Connect and TSC Console manage printer fleets, enabling swift deployment, configuration, and updates remotely.
- The Internal Embedded Webpage enables IT to remotely configure, troubleshoot, and oversee any specific printer in the field.

### Commitment to Sustainability

- 100% recyclable packaging reduces environmental waste.
- 100% recyclable printer casing with over 90% recyclable printer components.
- The optional linerless kit offers a sustainable solution for greener label printing.



[Click here for more information!](#)



**IPSi** INTEGRATED  
PRODUCTIVITY  
SYSTEMS

(844) 477-4911 | [www.ipsiscan.com](http://www.ipsiscan.com)

## Applications

### Manufacturing

- Work In Process
- Product Marking
- Compliance Labeling
- Industrial-Duty Printing

### Transportation and Logistics

- Packing
- Order Fulfillment
- Shipping/Receiving
- Inventory Management

### Retail

- Food and Beverage Packaging
- Product Label
- Weighing Scale

### Healthcare

- Specimen Labeling
- Asset or Inventory Label



# MB241 Series Specifications

| MODEL                    | MB241                                                                                                                                                                                                                                                                                                                                                                                                    | MB341                        | MB241T                        | MB341T                       |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-------------------------------|------------------------------|
| Resolution               | 8 dots /mm (203 dpi)                                                                                                                                                                                                                                                                                                                                                                                     | 12 dots /mm (300 dpi)        | 8 dots /mm (203 dpi)          | 12 dots /mm (300 dpi)        |
| Printing Method          | Thermal Transfer & Direct Thermal                                                                                                                                                                                                                                                                                                                                                                        |                              |                               |                              |
| Max. Print Speed         | 304.8mm (12") / second                                                                                                                                                                                                                                                                                                                                                                                   | 228.6mm (9") / second        | 304.8mm (12") / second        | 228.6mm (9") / second        |
| Max. Print Width         | 107mm (4.21")                                                                                                                                                                                                                                                                                                                                                                                            | 105.7mm (4.16")              | 107mm (4.21")                 | 105.7mm (4.16")              |
| Max. Print Length        | 25,400mm (1000")                                                                                                                                                                                                                                                                                                                                                                                         | 11,430mm (450")              | 25,400mm (1000")              | 11,430mm (450")              |
| Enclosure                | Die-cast based print mechanism/Metal cover with large clear media window                                                                                                                                                                                                                                                                                                                                 |                              |                               |                              |
| Physical Dimension       | 248mm (W) x 274mm (H) x 436mm (D)<br>9.76" (W) x 10.79" (H) x 17.17" (D)                                                                                                                                                                                                                                                                                                                                 |                              |                               |                              |
| Weight                   | 9.1kg (20.06lbs)                                                                                                                                                                                                                                                                                                                                                                                         |                              |                               |                              |
| Label Roll Capacity      | 203.2mm (8") O.D., 1" - 3" I.D. core                                                                                                                                                                                                                                                                                                                                                                     |                              |                               |                              |
| Ribbon                   | 450m with 1" ribbon core I.D., ink coated outside or inside                                                                                                                                                                                                                                                                                                                                              |                              |                               |                              |
| Ribbon Width             | 40mm - 110mm (1.6" - 4.3")                                                                                                                                                                                                                                                                                                                                                                               |                              |                               |                              |
| Processor                | 32-bit RISC CPU                                                                                                                                                                                                                                                                                                                                                                                          |                              |                               |                              |
| Memory                   | <ul style="list-style-type: none"> <li>256 MB Flash memory</li> <li>256 MB SDRAM</li> </ul>                                                                                                                                                                                                                                                                                                              |                              |                               |                              |
| Interface                | <ul style="list-style-type: none"> <li>RS-232</li> <li>USB 2.0</li> <li>Internal Ethernet, 10/100 Mbps</li> <li>USB host, for scanner or PC keyboard</li> <li>GPIO (dealer option)</li> <li>Internal Bluetooth (dealer option)</li> <li>Internal Bluetooth 5.0 MFi (factory option)</li> <li>Slot-in Wi-Fi 802.11 a/b/g/n/ac with Bluetooth 5.0 combo module (dealer option)</li> </ul>                  |                              |                               |                              |
| Power                    | <ul style="list-style-type: none"> <li>Internal universal switching power supply</li> <li>Input: AC 100 - 240V, 2.0A, 50 - 60Hz</li> <li>Output: DC 24V, 3.75A, 90W</li> </ul>                                                                                                                                                                                                                           |                              |                               |                              |
| LED/LCD                  | <ul style="list-style-type: none"> <li>2.3" color LCD</li> <li>1 LED (with 2 LEDs: green, red)</li> <li>3.5" color touch LCD</li> <li>1 LED (with 2 LEDs: green, red)</li> </ul>                                                                                                                                                                                                                         |                              |                               |                              |
| Operation Switch, Button | <ul style="list-style-type: none"> <li>1 power switch</li> <li>6 buttons (Menu, Pause/Feed, Up, Down, Left, Right)</li> </ul>                                                                                                                                                                                                                                                                            |                              |                               |                              |
| Sensors                  | <ul style="list-style-type: none"> <li>Gap transmissive sensor (position adjustable)</li> <li>Black mark reflective sensor (position adjustable)</li> <li>Ribbon encoder sensor</li> <li>Ribbon end sensor</li> <li>Head open sensor</li> </ul>                                                                                                                                                          |                              |                               |                              |
| Real Time Clock          | Standard                                                                                                                                                                                                                                                                                                                                                                                                 |                              |                               |                              |
| Internal Fonts           | <ul style="list-style-type: none"> <li>8 alpha-numeric bitmap fonts</li> <li>Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>                                                                                                                                                                                                                     |                              |                               |                              |
| Barcode                  | <ul style="list-style-type: none"> <li>1D barcode</li> <li>Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post</li> <li>2D barcode</li> <li>PDF-417, Micro PDF 417, Maxicode, DataMatrix, QR code, Aztec, TLC 39, RSS</li> </ul> |                              |                               |                              |
| Font & Barcode Rotation  | 0, 90, 180, 270 degree                                                                                                                                                                                                                                                                                                                                                                                   |                              |                               |                              |
| Printer Language         | TSPL-EZD (EPL, ZPL, ZPL II, DPL)                                                                                                                                                                                                                                                                                                                                                                         |                              |                               |                              |
| Media Type               | Continuous, die-cut, black mark, fan-fold, notched (outside wound)                                                                                                                                                                                                                                                                                                                                       |                              |                               |                              |
| Media Width              | 20mm - 120mm (0.8" - 4.7")                                                                                                                                                                                                                                                                                                                                                                               |                              |                               |                              |
| Media Thickness          | 0.06mm - 0.28mm (2.36mil - 11mil)                                                                                                                                                                                                                                                                                                                                                                        |                              |                               |                              |
| Media Core Diameter      | 25.4mm - 76.2mm (1" - 3")                                                                                                                                                                                                                                                                                                                                                                                |                              |                               |                              |
| Label Length             | 5mm - 25,400mm (0.2" - 1000")                                                                                                                                                                                                                                                                                                                                                                            | 5mm - 11,430mm (0.2" - 450") | 5mm - 25,400mm (0.2" - 1000") | 5mm - 11,430mm (0.2" - 450") |
| Environment Condition    | <ul style="list-style-type: none"> <li>Operation: 0°C to 40°C (32°F to 104°F), 25% - 85% non-condensing</li> <li>Storage: -40°C to 60°C (-40°F to 140°F), 10% - 90% non-condensing</li> </ul>                                                                                                                                                                                                            |                              |                               |                              |
| Safety Regulation        | CB, FCC Class A, CE Class A, UKCA, RCM Class A, cTUVus, TÜV, IC Class A, NOM, VCCI, CCC, BIS, KC, BSMI, EAC, ENERGY STAR®                                                                                                                                                                                                                                                                                |                              |                               |                              |
| Environmental Concern    | Comply with RoHS, WEEE                                                                                                                                                                                                                                                                                                                                                                                   |                              |                               |                              |
| Accessories              | <ul style="list-style-type: none"> <li>Quick start guide</li> <li>USB cable</li> <li>Power cord</li> </ul>                                                                                                                                                                                                                                                                                               |                              |                               |                              |
| Limited Warranty         | <ul style="list-style-type: none"> <li>Printer: 2 years</li> <li>Print head: 25km (1 million inches) or 12 months which comes first</li> <li>Platen: 50km (2 million inches) or 12 months which comes first</li> </ul>                                                                                                                                                                                   |                              |                               |                              |
| Factory Option           | Internal Bluetooth 5.0 MFi                                                                                                                                                                                                                                                                                                                                                                               |                              |                               |                              |
| Dealer Option            | <ul style="list-style-type: none"> <li>Peel-off kit</li> <li>Regular guillotine cutter (full cut)</li> <li>5" O.D. internal rewinder kit</li> <li>GPIO</li> <li>Linerless tear-off kit</li> <li>Linerless cutter kit</li> <li>Slot-in Wi-Fi 802.11 a/b/g/n/ac with Bluetooth 5.0 combo upgrade kit*</li> <li>Internal Bluetooth 5.0 module**</li> </ul>                                                  |                              |                               |                              |
| User Option              | <ul style="list-style-type: none"> <li>Slot-in Wi-Fi 802.11 a/b/g/n/ac with Bluetooth 5.0 combo module (for device with slot-in housing)</li> <li>KP-200 Plus keyboard display unit</li> <li>Universal cutter tray</li> </ul>                                                                                                                                                                            |                              |                               |                              |

\* Either GPIO or Wireless interface is available.

\*\* Choose between a Wi-Fi with Bluetooth combo or an internal Bluetooth interface option.



## TSC

**CORPORATE HEADQUARTERS**  
TSC Auto ID Technology Co., Ltd.  
Tel: +886 2 2218 6789  
E-mail: apac\_sales@tscprinters.com

**LI ZE PLANT**  
TSC Auto ID Technology Co., Ltd.  
Tel: +886 3 990 6677  
E-mail: apac\_sales@tscprinters.com

**AMERICAS**  
TSC Auto ID Technology America Inc.  
Tel: +1 657 258 0808  
E-mail: americas\_sales@tscprinters.com

**MEXICO**  
TSC Mexico Representative Office  
Tel: +1 52 (33) 3673 1406  
E-mail: americas\_sales@tscprinters.com

**BRAZIL**  
TSC Brazil Representative Office  
Tel: +55 (11) 3554 7225  
E-mail: americas\_sales@tscprinters.com

**EMEA**  
TSC Auto ID Technology EMEA GmbH  
Tel: +49 (0) 8106 37979 000  
E-mail: emea\_sales@tscprinters.com

**RUSSIA**  
TSC Auto ID Technology EMEA GmbH  
Tel: +7 495 646 3538  
E-mail: emea\_sales@tscprinters.com

**MIDDLE EAST**  
TSC Auto ID Technology ME Ltd, FZE  
Tel: +971 4 2533 069  
E-mail: emea\_sales@tscprinters.com

**ASIA PACIFIC**  
TSC Auto ID Technology Co., Ltd.  
Tel: +886 2 2218 6789  
E-mail: apac\_sales@tscprinters.com

**INDIA**  
TSC India Representative Office  
Tel: +91 2249 679 315  
E-mail: apac\_sales@tscprinters.com

**CHINA**  
Tianjin TSC Auto ID Technology Co., Ltd.  
Tel: +86 22 5981 6661  
E-mail: apac\_sales@tscprinters.com

**KOREA**  
TSC Korea Representative Office  
Tel: +82 2 852 3322  
E-mail: apac\_sales@tscprinters.com



TSC® is a trademark of TSC Auto ID Technology Co., Ltd.  
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.  
© 2024 TSC Auto ID Technology Co., Ltd.  
Product models and Specifications are subject to change without notice.  
Contact your TSC sales representative for specific information.  
20240522

**Click here for more information!**

**IPSi** INTEGRATED  
PRODUCTIVITY  
SYSTEMS  
(844) 477-4911 | [www.ipsiscan.com](http://www.ipsiscan.com)

[www.tscprinters.com](http://www.tscprinters.com)