

TSC

The Smarter Choice.



Click here for more information!



**INTEGRATED
PRODUCTIVITY
SYSTEMS**

(844) 477-4911 | www.ipsiscan.com



TDP-225 SERIES – Desktop Direct Thermal Bar Code Printers **OFFERS BIG FEATURES FOR SMALL AREAS**



KEY FEATURES

- High quality double-walled clamshell design
- 127 mm (5") OD media capacity
- Up to 127 mm (5") per second print speed
- Available in 203 dpi and 300 dpi resolutions
- Easy media loading
- Head open sensor
- microSD Flash memory expansion up to 4 GB
- Serial and USB 2.0 connectivity
- Optional front LCD display, internal Ethernet, peel-off module, cutter module, Bluetooth module, and stand-alone keyboard
- ENERGY STAR® qualified
- Cerner certified

APPLICATIONS

- Jewelry Tags
- Retail Point-Of-Sale
- Shelf Labeling
- Product Marking
- Healthcare Specimen Labeling
- Healthcare Patient Tracking
- Inventory & Asset Management
- Small Office or Home Office Mailing
- Shipping
- File-Folder Labeling

TDP-225 SERIES – Desktop Direct Thermal Bar Code Printers

PRINTER MODEL		TDP-225	TDP-324
Resolution	8 dots/mm (203 DPI)		12 dots/mm (300 DPI)
Printing method	Direct Thermal		
Max. print speed	127 mm (5")/second		102 mm (4")/second
Max. print width	54 mm (2.13")		48 mm (1.89")
Max. print length	2,286 mm (90")		1,016 mm (40")
Enclosure	Clamshell design with wall mount hole at the bottom cover		
Physical dimension	109 mm (W) x 171 mm (H) x 209 mm (D) 4.29" (W) x 6.73" (H) x 8.23" (D)		
Weight	1.2 kg (2.65 lbs)		
Label roll capacity	127 mm (5") OD		
Processor	32-bit RISC CPU		
Memory	• 4 MB Flash memory • 8 MB SDRAM • microSD card reader for Flash memory expansion, up to 4 GB		
Interface	• RS-232 • USB 2.0 • Internal Ethernet, 10/100 Mbps (dealer option) • Bluetooth (user option)		
Power	External universal switching power supply • Input: AC 100-240V, 1A, 47-63Hz • Output: DC 24V, 2.08A, 50W		
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)		
Sensors	• Transmissive gap sensor • Black mark reflective sensor (position adjustable) • Head open sensor		
Real time clock	Standard		
Internal fonts	• 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font • 1D bar code		
Bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11		
	• 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec		
Font and barcode rotation	0, 90, 180, 270 degree		
Printer language	TSPL-EZ™		
Media type	Continuous, die-cut, black mark, fan-fold, notched, wristband (outside wound)		
Media width	15 ~ 60 mm (0.59" ~ 2.36")		
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)		
Media core diameter	25.4 ~ 38 mm (1" ~ 1.5")		
Label length	10 ~ 2,286 mm (0.39" ~ 90")		10 ~ 1,016 mm (0.39" ~ 40")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10~ 90% non-condensing		
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC, ENERGY STAR®		
Environmental concern	Comply with RoHS, WEEE		
Accessories	• Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply		
Limited warranty	• Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first		
Factory options	• 128 x 64 pixels graphic type LCD display with back light		
Dealer options	• Internal Ethernet interface (10/100 Mbps) • Peel-off module • Guillotine cutter (full cut and partial cut)		
User options	• Bluetooth module (serial interface) • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard		



TSC
The Smarter Choice.

CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +52 (33) 3165 7379
E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 99597 8098
E-mail: americas_sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 00
E-mail: emea_sales@tscprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 495 249 9017
E-mail: emea_sales@tscprinters.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com



TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2017 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.